

Static Dissipative
Safety Shoes
M05A-012-WH



Cleanroom & ESD Footwear



Conductive Shoes

Out Sole	PVC outsole	Inner Sole	ESD insole
Upper	PVC Synthetic Leather	Volume Resistance	10e4 ~ 10e6 ohm
Size	220, 225, 230, 235, 240, 245, 250, 255, 260, 265, 270, 275, 280, 290, 300 mm		
Features	- Reliable steady resistance (conductive) - No marking on the floor		



Item Code M07A-009
Model BCS-320



Item Code M07A-012
Model BCS-321



Item Code M07A-013
Model BCS-322



Item Code M07A-014
Model BCS-323



Item Code M07A-015
Model BCS-324



Item Code M07A-011
Model BCS-328

Static Dissipative Shoes

Out Sole	PVC outsole	Inner Sole	ESD insole
Upper	PVC Synthetic Leather	Volume Resistance	10e6 ~ 10e8 ohm
Size	220, 225, 230, 235, 240, 245, 250, 255, 260, 265, 270, 275, 280, 290, 300 mm		
Features	• Cost - effective and popular design • Anti-slip • Abrasion resistant • Low particle generation • Durable and long-lasting • Good wearability		



Item Code M01A-002
Model BSS-311



Item Code M01A-003
Model BSS-312



Item Code M01A-005
Model BSS-314



Item Code M01A-007
Model BSS-318

Out Sole	PU outsole	Inner Sole	ESD insole
Upper	PU Synthetic Leather	Volume Resistance	10e6 ~ 10e8 ohm
Size	220, 225, 230, 235, 240, 245, 250, 255, 260, 265, 270, 275, 280, 290, 300, 310, 320 mm		
Features	• Light weight • Recyclable PU outsole • Comfortable cushion • Abrasion resistant • Low particle generation		



Item Code M01A-008
Model BUS-370



Item Code M01A-009
Model BUS-371



Item Code M01A-011
Model BUS-374



Item Code M01A-012
Model BUS-378



Static Dissipative Shoes

Out Sole	PU outsole	Inner Sole	ESD Fabric + Soft EVA Sponge
Upper	Different by each model	Volume Resistance	10e6 ~ 10e8 ohm
Color	White (WH), Green (GE), Grey (GR), Navy (NA)		
Size	225, 230, 235, 240, 245, 250, 255, 260, 265, 270, 275, 280, 290, 300 mm		
Features	• High density PU foam out sole • Excellent shock absorption • New ergonomic design • Direct injection moulding • Durable and long-lasting • Anti-slip • Low particle generation		



Item Code M01A-024
Upper PVC Synthetic Leather



Item Code M01A-025
Upper PVC Synthetic Leather + Polyester Mesh



Item Code M01A-026
Upper PVC Synthetic Leather + Polyester Mesh + 20 mm Nylon Velcro



Item Code M01A-027
Upper PVC Synthetic Leather + Polyester Mesh + 20 mm Nylon Velcro



Item Code M01A-028
Upper PVC Synthetic Leather + 20 mm Nylon Velcro



*Air Cushion (TPU)

Item Code M01A-029
Upper PU Synthetic Leather + Polyester Mesh + Air cushion included



Item Code M01A-030
Upper Polyester two-fold Mesh + PVC Leather tape



Design for good ventilation

(M01A-025 / M01A-026 / M01A-027 / M01A-028 / M01A-029 / M01A-030)



Velcro for easy wearing & taking off

(M01A-026 / M01A-027 / M01A-028)

Static Dissipative Shoes New

(Mesh Standard Type, Mesh Velcro Type, Closed Type)



M01A-031

M01A-032

M01A-033

Out Sole	Anti-static PU outsole
Insole	ESD Insole
Upper	PVC Upper
Volume Resistance	10e6 ~ 10e8 ohm
Size	230, 235, 240, 245, 250, 255, 260, 265, 270, 275, 280, 285, 290, 300 mm
Features	• The midsole is made with check conductive fabric, providing more stable resistance values compared to standard striped types, making it ideal for electrostatic control. • The lightweight PU outsole minimizes worker fatigue during extended use. • A protective heel pad is added to increase durability and extend product life.

Static Dissipative Safety Shoes

Out Sole	PU outsole	Inner Sole	T/C fabric insole
Upper	PU Synthetic Leather	Toe cap	Steel toe cap
Color	White (WH), Black (BK)	Volume Resistance	10e7 ~ 10e9 ohm
Size	225, 230, 235, 240, 245, 250, 255, 260, 265, 270, 275, 280, 290, 300 mm		
Features	• Recyclable PU outsole • Durable and long-lasting • Anti-slip • Oil resistant • Abrasion resistant • Shock absorption		



Item Code M05A-001-WH
Model BTU-510



Item Code M05A-002-WH
Model BTU-515



Item Code M05A-001-BK
Model BTU-510



Item Code M05A-002-BK
Model BTU-515

Out Sole	PU outsole	Taping	PVC
Inner Sole	Small diaper grid fabric + Conductive Thread	Toe cap	Steel toe cap
Upper	Wet PU (Polyurethane) + Non-woven + Merry Mesh Lining	Volume Resistance	10e6 ~ 10e8 ohm
Size	230, 235, 240, 245, 250, 255, 260, 265, 270, 275, 280, 290, 300 mm		



M05A-012-WH



M05A-013-WH



M05A-012-BK



M05A-013-BK

Item Code	M05A-014
Out Sole	PU with ESD Compound
Middle Sole	Penetration Resistant Inserted Insole
Inner Sole	Static Control Polyester fabric + E.V.A.
Upper	Synthetic Leather + Merry Mesh Lining
Toe cap	Steel toe cap (604H)
Volume Resistance	10e7 ~ 10e9 ohm
Size	220, 225, 230, 235, 240, 245, 250, 255, 260, 265, 270, 275, 280, 285, 295, 300, 310 mm



Item Code	M05A-015
Out Sole	ESD PU (PU + ESD Material)
Middle Sole	Boi-ceramic ESD fiber (3 mm Latex)
Upper	PU Synthetic Leather (1.4 mm Thickness)
Pad	PU Interlock 5 mm Latex Cushion
Toe cap	Steel toe cap (604H)
Volume Resistance	10e7 ~ 10e9 ohm
Size	225, 230, 235, 240, 245, 250, 255, 260, 265, 270, 275, 280, 290, 300 mm



Static Dissipative Safety Shoes

Item Code	M05A-011
Out Sole	PU outsole & Air cushion
Inner Sole	Polyester + PVC Dots
Upper	Wet PU 1.5 mm + Non-Woven 0.9 mm(T) + Merry Mesh Lining
Toe cap	Steel toe cap
Volume Resistance	10e7 ~ 10e9 ohm
Size	225, 230, 235, 240, 245, 250, 255, 260, 265, 270, 275, 280, 290, 300 mm



*Air Cushion (TPU)

Static Dissipative Slippers

Out Sole	PU outsole	Inner Sole	ESD PU or PVC insole
Upper	PU Synthetic Leather	Volume Resistance	10e6 ~ 10e8 ohm
Size	220, 230, 240, 250, 260, 270, 280, 290 mm		
Features	• Good wearability for daily use • Durable and long-lasting • Low particle generation		



Item Code M03A-001
Model BPU-420



Item Code M03A-006
Model BPU-426



Item Code M03A-007
Model BPU-427

Out Sole	PU outsole	Color	Black (BK), Grey (GR)
Upper	PVC Synthetic Leather + PVC 0.4 mm tape	Volume Resistance	10e6 ~ 10e8 ohm
Size	230, 240, 250, 260, 270, 280, 290, 300 mm		
Features	• Good wearability for daily use • Durable and Long-lasting • Low particle generation		



VIDEO



Item Code M03A-014-BK-size



Item Code M03A-014-GR-size



*Air Cushion (TPU)

ESD Anti-Fatigue Slippers

Out Sole	Foamed PU and Conductive NBR pad
Upper	Laminated wet PU + 4 mm PU sponge laminated polyester fabric
Volume Resistance	10e5 ~ 10e6 ohm
Size	220, 230, 240, 250, 260, 270, 280, 290 mm
Features	• Ease the stress on feet • Ergonomic designed sole



Item Code M25A-002

Static Dissipative Boots

Out Sole	PVC outsole	Inner Sole	ESD insole
Upper	PVC Synthetic Leather	Volume Resistance	10e6 ~ 10e8 ohm
Leggings	Lint free ESD fabric leggings		
Size	220, 225, 230, 235, 240, 245, 250, 255, 260, 265, 270, 275, 280, 290, 300 mm		
Features	• Cost - effective • Anti-slip • Abrasion resistant • Low particles generation • Durable and long-lasting • Good wearability • Cleanroom applicable		

Item Code M02A-001
Model BSB-330Item Code M02A-002
Model BSB-333

Out Sole	PU outsole	Inner Sole	T/C fabric insole
Upper	PU Synthetic Leather	Volume Resistance	10e7 ~ 10e9 ohm
Leggings	Lint free ESD fabric leggings		
Size	225, 230, 235, 240, 245, 250, 255, 260, 265, 270, 275, 280, 290, 300, 310, 320 mm		
Features	• Cost - effective design • Light weight • Durable and long-lasting • Cleanroom applicable		

Item Code M02A-003
Model BUB-381SItem Code M02A-004
Model BUB-382Item Code M02A-005
Model BUB-383

Static Dissipative Boots

Out Sole	PU outsole
Inner Sole	ESD insole
Upper	1.4 mm (T) PVC Synthetic Leather 0.5 mm (T) PVC Synthetic Leather Tape
Leggings	Static Dissipative Lint Free Fabric
Others	Sewing Thread made of Filament Yarn, Zipper, Elastic Band
Volume Resistance	10e6 ~ 10e8 ohm
Size	225, 230, 235, 240, 245, 250, 255, 260, 265, 270, 275, 280, 290, 300 mm



Item Code M02A-025
Model BUB-391

Static Dissipative Safety Boots

Out Sole	PU outsole	Inner Sole	T/C insole
Upper	PU Synthetic Leather	Leggings	Lint free ESD fabric leggings
Toe cap	Steel toe cap	Volume Resistance	10e7 ~ 10e9 ohm
Size	225, 230, 235, 240, 245, 250, 255, 260, 265, 270, 275, 280, 290, 300 mm		
Features	- Recyclable PU outsole - Durable and long-lasting - Anti-slip - Oil resistant - Abrasion resistant - Shock absorption - Low particle generation - Cleanroom applicable		



Item Code M06A-001
Model BTU-530



Item Code M06A-002
Model BTU-533



Steel toe cap



Item Code M06A-009

Out Sole	PU outsole
Inner Sole	Small diaper grid fabric + Conductive Thread
Upper	Wet PU (Polyurethane) + Non-woven + Merry Mesh Lining
Leggings	Lint free ESD fabric leggings
Toe cap	Steel toe cap
Volume Resistance	10e6 ~ 10e8 ohm
Size	230, 235, 240, 245, 250, 255, 260, 265, 270, 275, 280, 290, 300 mm

Conductive Boots

Out Sole	Conductive PVC outsole
Inner Sole	ESD insole
Upper	PVC Synthetic Leather
Leggings	Lint free ESD fabric leggings
Volume Resistance	10e4 ~ 10e6 ohm
Size	220, 225, 230, 235, 240, 245, 250, 255, 260, 265, 270, 275, 280, 290, 300 mm
Features	• Reliable steady resistance (conductive) • No marking on the floor • Cleanroom applicable



Item Code M08A-001
Model BCB-340

Conductive Overboots

Out Sole	Conductive PVC outsole
Leggings	Lint free ESD fabric leggings + Nylon strap and buckle
Volume Resistance	10e4 ~ 10e6 ohm
Size	XS, S, M, L, XL
Features	• Cost-effective • Soft and flexible • Reliable steady resistance (conductive) • No marking on the floor



Item Code M10A-001
Model BCO-360

Static Dissipative Overboots

Out Sole	Static dissipative fishbone designed hypalon sole (Chlorosulfonated Polyethylene (CSM) + Natural rubber + Conductive Compound)
Leggings	Lint-free cleanroom fabric + Polyester strap with snap buttons and buckle
Volume Resistance	10e7 ~ 10e9 ohm
Size	XS, S, M, L, XL, 2XL, 3XL
Features	• Autoclavable • Sterilization compatible • Soft and flexible • Gamma radiation compatible • Slip resistant • Oil & chemical resistant • High washing temperature



Item Code M04A-002
Model NHB-370

Static Dissipative Hypalon Soles

RTG (ohm)	10e7 ~ 10e9	
Material	- Chlorosulfonated Polyethylene (CSM) - Natural Rubber	
Features	- Cleanroom Applicable - Sterilization Compatible - Autoclavable - Gamma Radiation Compatible - Slip Resistant	



Item Code M11A-002
Model PHS-110F

Size	XS	S	S/M	M	M/L	L	L/XL	XL	2X	3XL
Length × Width (mm)	245 × 100	265 × 108	275 × 110	290 × 118	302.5 × 123	315 × 128	327.5 × 133	340 × 138	365 × 148	375 × 150
Weight (g/pr) ± 5%	220	255	270	320	345	365	380	410	465	530

RTG (ohm)	10e7 ~ 10e9	
Materials	- Chlorosulfonated Polyethylene (CSM) - Natural Rubber	
Features	- Cleanroom Applicable - Sterilization Compatible - Autoclavable - Gamma Radiation Compatible - Slip Resistant	



Item Code M11A-003
Model PHS-120P

Size	XS	S	S/M	M	M/L	L	L/XL	XL	2X	3XL
Length × Width (mm)	-	265 × 108	-	290 × 118	-	315 × 128	-	340 × 138	365 × 148	375 × 150
Weight (g/pr) ± 5%	-	255	-	320	-	365	-	410	465	530

Conductive NBR Soles

RTG (ohm)	10e6 ~ 10e7	
Materials	- Synthetic Rubber (NBR-35L) - Natural Rubber	
Features	- Cleanroom Applicable - Autoclavable - Silicone & Phthalate Free - Sterilization Compatible - Gamma Radiation Compatible - Slip Resistant	



Item Code M11A-006
Model PRS-140C

Size	XS	S	S/M	M	M/L	L	L/XL	XL	2X	3XL
Length × Width (mm)	245 × 100	265 × 108	275 × 110	290 × 118	302.5 × 123	315 × 128	327.5 × 133	340 × 138	365 × 148	375 × 150
Weight (g/pr) ± 5%	220	255	270	320	345	365	380	410	465	530

Static Dissipative Flat Soles



VIDEO

RTG (ohm)	10e6 ~ 10e7
Materials	• Synthetic Rubber (NBR-35L) • Natural Rubber
Features	• Cleanroom Applicable • Sterilization Compatible • Autoclavable • Gamma Radiation Compatible • Soft & Flexible • Light Weight • Slip Resistant



Item Code M11A-004
Model PRS-130E

Size	XS	S	S/M	M	M/L	L	L/XL	XL	2X	3XL
Length × Width (mm)	278 × 120	298 × 117	-	317 × 125	-	330 × 132	-	348 × 135	357 × 140	370 × 147
Weight (g/pr) ± 5%	148	156	-	180	-	194	-	236	256	260

Conductive Grey Soles

RTG (ohm)	10e4 ~ 10e6
Material	PVC
Features	• Reliable steady resistance (conductive) • Slip Resistant




Item Code M11A-001
Model SUO-442

Size	XS	S	S/M	M	M/L	L	L/XL	XL	2X	3XL
Length × Width (mm)	260 × 108	290 × 110	-	310 × 118	-	330 × 128	-	350 × 133	-	-
Weight (g/pr) ± 5%	270	330	-	370	-	400	-	410	-	-

Accessories for Overboots

Polyester Strap for Buckles

M16A-001



Size: 20 mm x 100 m/roll

Reinforced ESD Fabric

M03F-006



Size: 60" x 100 m/roll

Autoclavable Buckles (2pcs)

M16A-004



20 mm(W), white

Webbing for Overboots

M16A-002



Size: 40 mm x 100 m/roll





CSM Rubber Sheet for Soles

The CSM (Chlorosulfonated polyethylene) rubber sheet reinforced with high tenacity polyester fabric is a kind of a very particular material for the bottom soles of cleanroom overshoes or the webbing material on the overshoes. Coming in a sheet form, it can be applied to the various shapes and the sizes of the soles according to each customer's need, unlike many existing ready-made soles.




Features

- Excellent chemical resistance
- Anti-slip
- Bendable at a low temperature (-45°F)
- Strong resistance to abrasion
- Autoclavable (withstand up to 120°C)
- Gamma-ray stable at min. 737 kGy/max. 760.8 kGy
- Antistatic finish (10e10 ~ 10e11 ohm)



Item Code	M20F-001
Packing	30 yds/roll
Constructions	 • Polyester fabric (front) • CSM Rubber (back)

Test	Warp	Weft	Unit	Test Method
Color	Light Grey			Visual
Width (trimmed)	56		inch	ASTM D 751-19
Total Weight	1,010.8 (23.8) ±5%		g/m ² (oz/yd ²)	
Thickness	0.87 ± 0.10 mm		mm	
Bursting Strength	Above 1,050		kPa	
Tearing Strength	80 (18.0)	57 (12.8)	N (lbf)	FS 191A-5134 : 1978
Breaking Strength	2,092.7 (470.5)	1,463.1 (328.9)	N (lbf)	ASTM D 751-19 GRAB test method
Elongation	50.4	53.5	%	
Adhesion Strength	157.4 (30.3)		N/2.54 cm (lbf/inch)	FS 191A 5970 : 1978
Abrasion Resistance	1,066		cycles	ASTM D 3389-21



Antimicrobial EVA Clogs New

Features

- Eco-Friendly EVA material
- Good Ventilation (E01A-001)
- Antimicrobial (99.9%) treated Insole
- Slip-resistant Outsole
- Foldable rear Strap (E01A-001)
- Washable & Quick dry
- Lightweight & Soft feeling
- Waterproof (E01A-002)

Applications

- Hospital, Kitchen, etc.



Item Code		E01A-001
Material	Upper & Outsole	EVA (White - Antimicrobial)
	Insole	EVA (Antimicrobial)
Strap		PVC
Size		230, 240, 250, 260, 270, 280 mm
Width		9.5 cm (230 mm)
Height		9.0cm (230 mm)
Heel height		2 cm
Colors		White, Grey, Navy 

Item Code		E01A-002 (type A)	E01A-003 (type B)
Material	Upper	EVA (White - Antimicrobial)	
	Insole	EVA (Antimicrobial)	
	Outsole	PVC foam, Rubber (Non Slip)	
Size		230, 240, 250, 260, 270, 280 mm	
Width		9.5 cm (230 mm)	
Height		9.8 cm (230 mm)	
Heel height		1.5 cm	
Colors		White, Purple, Navy, Wine, Black 	



Type A



Type B